

31/08/05

10/552633

JC09 Rec'd PCT/PTO 17 OCT 2005

1

+

WO 2004/089075

PATENT

PCT/CH 2004/000254

DESCRIPTION

TITEL

Method for the control of harmful Micro-Organisms and Insects in crop protection with means of dipole-electrical Air-Jet Spray-Technology, ozonated Water and UV-C irradiation.

TECHNICAL FIELD

The invention concerns a new crop-protection-method with Ozone and UV-C-Light, and the applied techniques for the implementation of the process according to the preamble of the independent patent claims.

STATE OF THE PRESENT USED TECHNIQUE

For the fight against harmful insects, fungus, bacteria, virus and yeast and other pathogens, high toxic chemicals and substances are used in plant protection up to date, which are toxic residues on crops, created resistances in pests and have a heavy impact on the environment and are also very expensive.

The use of poisonous chemicals for crop protection is therefore today heavily contested and consumers prefer well priced ecologically and bio-environmentally friendly products without toxic contents as residues.

With the new invention, the application of ozonated water and UV-C light and with and new Spray Technology all kinds of plant pathogens can be controlled without the use of toxic, environment damaging and resistance creating substances.

The new plant protection technology is clean, substantially cheaper, equally efficient and over all environmentally friendly and can also be used in ecologically natural growing.

PRESENTATION OF THE INVENTION

The aim of the invention is the presentation of a new, cost efficient environmentally friendly and ecologically procedure for the protection of plants against harmful insects, bacteria, virus, yeast without creating residues and resistancy by chemicals with the use of ozone containing Water, Dipole-electrical Air Job Spray – Technology with a wetting agent and UV-Light.

INTRODUCTION

Ozone, O₃ is the 3 atomic form of oxygen.

Ozone is highly reactive and the most powerful known oxidation media. It is 51 times more reactive than chlorine and 3125 times faster in the destruction of microorganisms.

Ozone is a highly unstable molecule in gaseous form which disintegrated in a short period of time (half – life time ca. 20 minutes) again in oxygen.

Ozone is created by UV-C radiation or by Corona Cathodic discharge with approximately 7,000 volts.

Ozone is better soluble in water than oxygen.

Ozone is a gas of bluish color, heavy smelling and with an exposition concentration of 0.1 mg per m³/air unproblematic for permanent exposure.

Ozone reacts through the splitting of an oxygen atom when having contact with organic or inorganic compound and leads through the formation of Hydroxy-Radicals to an oxidation respectively to a gradual dissolution of cell walls and membranes of eucariontes which are resulting in the destruction of fungus, bacteria, virus, yeast and their spores, and which are paralyzing the respiration organs of insects which consequently results in death.

Ozone can not penetrate through the respiration stomata, only in long exposure where it creates in the plant System Acquired Resistance (SAR).

Ozone alone works in a short contact principle and has itself no systemic effect.

Ozone does not have residues since it disintegrates in a short period of time again in oxygen.

Ozone leaves no damaging effects on plants because of its short action time.

At the same time, ozone creates no resistances in microbes or plant pathogens.

Ozone is therefore, a most effective biocide against fungus, bacteria, virus, yeast, biofilms and protozoa and high creatures like insects, worms, aphids and other pathogenic parasites.

Ozone is permitted by the FDA (Food and Drug Administration) as additive since the 26 June of 2001 in direct contact with foodstuff.

Ozone is also permitted by EPA (Environment Protection Agency) in USA.

UV –C Light as electromagnetic direct radiation has its optional biocidal effect in the wave length spectrum of 254 nanometers against bacteria, yeast, virus and insects.

The irradiation provokes in microorganisms a dissolution of cell-membranes and is destructive to DNA and RNA structures.

In the wave length range of 185 nanometers UV-C radiation creates ozone which under the influence of high humidity generates high oxidative label hydroxyl radicals which increase the effect of the ozone as a biocide.

(The efficiency of ozone as a biocide micro biotic Hurdle Principal)

UV-C irradiation of foodstuff is permitted by the FDA USA (Food and Drug Administration) since 1997 and for vegetable foodstuff also in the radiation protection order of Germany.

For the efficiency of the UV-C irradiation, the radiation dose is essential, which is expressed as mW/sec/cm² (Milli Watt per second per square centimeters of irradiated surface).

The dose to eliminate of microorganisms is preferentially 4,000 to 15,000 mW/sec/cm² (depending on species).

Insects ca. 500,000 – 1,500.000 mW/sec/sec/cm² (depending on species)

The inventor has confirmed during 10 years of research work in the laboratory and in extensive field trials, the efficiency of the new crop – protection method with ozonated water and UV irradiation and the corresponding application technology.

The new crop protection method reaches an efficiency of 92% in mixed infections and simultaneously attack of three (3) insects varieties in weed and bush beans, tomatoes and cucumbers in open air and as well in greenhouse production. Other crops in which the invention was tested and which were treated preventive have not shown any harvest reducing damages.

To the knowledge of the inventor, no scientific work was published as of today in this field of crop protection with ozone and UV – light and with the corresponding Applications – technique for the field application.

THE SOLUTION OF THE TASK

The solution to achieve the task is described in the definition of the independent patent claimed.

According to the invention a process used for the application in crop protection against pathogenic fungus, yeast, bacteria, spores and insects indicates the kind and specifications of biocides (Ozone and UV – C radiation) and the procedure and specifications of the process of this generation, and the way and specifications of the method's technology for an efficient application.

The invention is an integrated system in which the technical components of the ozone and UV – generation and the application technology are integrated in the form of tractor - a trailed or tractor hydraulic mounted spray machine or a hand operated knapsack spray gun.

At the same time, the emphasis of the invention lies not only in the combination of ozone and UV–C radiation as a new application and hurdle – technology for the pest control in crop protection but also in the combined new application technologies, in the dipole electrical spray – method and the air – jet spray technology.

The new combined application technology plays an essential part for the successful employment of ozone and UV – C radiation and fulfills all parameters for an optional effect of the crop protection method.

Without the special application technique, the efficiency of ozone and UV-C radiation is insufficient since the effect of ozone is very volatile and short because of its high molecular instability.

Furthermore the invention is innovative regarding the method of ozonisation of the water with means of a Venturi bulb and the following injection with the turbine, which was especially designed for this application purpose.

With this new injection technique of the extensive mixing of ozone with the spray waters and with the combination of an inorganic wetting agent, the ozone concentration in the dissolved gas bubbles can be up to 17% and has a threefold remaining capacity in the water (up to 1 hour) without the fact that ozone gas is transforming to oxygen. With such means the efficacy of ozone as a biocide can be substantially increased.

The invention of the new crop protection technology consists in the combination of the creation of ozonated water (1. biocide), in the intermediate tank storage of the ozonated water and in the atomization – spraying of the biocide with the dipole electrical spray technology and direct UV – C irradiation (2. biocide).

The new application methods for the crop protection with ozone containing water and UV-C irradiation consists of the following technical compounds:

1. Pre – spray installation, preferentially PTO – shaft or electrically driven, preferentially in form of a tractor boom-sprayer with tank for the pre-wetting of plants with negatively charged water that may contain an inorganic wetting agent with

means on the boom mounted water – spray and air-jet whirl stream nozzles, UV-C radiation lamps and boom sprayer protection-cover adaptable for the exact tuning of the spray-mist and the UV-C irradiation.

The pre-spray installation comprises the following technical main parts:

- 1A. Three (3) point hydraulic chassis with tank holders.
- 2A. PTO-shaft connection or electro meter
- 3A. Tank for water filling
- 4A. Sprayer Pressure – Pump
- 5A. Two (2) pressure Manometers adjustable (entrance and exit pressure)
- 6A. Two (2) lateral spray –booms with preferable twenty (20) UV – lamps minimum 35 Watts
- 7A. One (1) anode
- 8A. One (1) Transformer for alternating and direct current for the negative charging of the spray water.
- 9A. One (1) Air – blower or air –compressor with pressure tank for the creation of the air – jet stream.
- 10A. Divers spray nozzle for water and air.
- 11A. One (1) water-dosing valve.
- 12A. One (1) reverse pressure valve for water mixer in the tank with handle.
- 13A. One (1) filling gate for water with pressure seal.
- 14A. One (1) Tank drainage gate valve.
- 15A. One (1) Spray boom cover adaptable for the precise guidance of spray- mist air-whirl- stream and UV light.
- 16A. One (1) PTO-shaft connection for spray pressure – pump.

2. Pulled or hydraulic mounted telescopic boom sprayer PTO-shaft or electrical driven for the spraying of ozonated water via water spraying nozzles with UV-C lamps and Spray boom cover for the precise tuning of the spray and air-stream and the UV- irradiation.

The ozone water spray equipment contains the following technical main parts:

- 1B. Three (3) point hydraulic chassis with tank holders.
- 2B. One (1) electrical generator with control box.
- 3B. One (1) Air separator for the production of oxygen.
- 4B. One (1) generator with cathodic discharge from 98% oxygen.
- 5B. One (1) ozone-dosing valve
- 6B. One (1) Ozone in water concentration analysis
- 7B. One (1) Venturi valve for the injection of ozone in water.
- 8B. One (1) electrical pressure pump for water tank.
- 9B. Two (2) pressure manometer (entrance and exit pressure pump with 2 gate valve.
- 10B. Ozone –gas mixer turbine
- 11B. One (1) water tank for ozonated water
- 12B. One (1) driving –chassis or mounting device for tractor hydraulic
- 13B. PTO shaft or electrical driven water pressure pump made of rust free steel for the spraying of ozone – water.
- 14B. Two (2) lateral telescopic sprays – booms with minimum 20 mounted 35 Watts UV – C lamps.
- 15B. Divers Ozone Water Spray and air – jet whirl stream nozzles.
- 16B. One (1) PTO shaft or electrical driven air – blower or air – compressor with Pressure tank to perform the air whirl stream via the nozzles.
- 17B. One (1) water-dosing valve
- 18B. Two (2) pressure manometers (entrance and exit – pressure)

- 19B. One (1) reverse pressure valve for water – mixer in tank
- 20B. One (1) filling gate for water in the tank with pressure seal
- 21B. One (1) tank drainage valve
- 22B. One (1) Spray – boom protection cover, adjustable for the precise guidance of the air and whirl stream and the UV – irradiation

3. Pulling and Mounting Equipment

Tractor (minimum 65 HP) with front and back – hydraulic system, with adjustable PTO-shaft drive at front and back, with closed drivers cabin with over – pressure ventilation and ozone – filters.

The new application process of the invention consists of two major steps:

1. Complete pre – wettening of the plants to be treated with negative charged water and with inorganic wettening agent with the help of the dipole – electrical air – whirl stream technology (air- jet) and UV – irradiation by UV – C lamps.

This pre-treatment of plants is necessary that with the immediately following ozonated water spray treatment all parts of plants are coming in contact with ozone (reactive oxidizing radicals) and that the ozonated water is distributed on the leaves regularly in form of a film.

Through the air- whirl stream of the electrostatic spray nozzles on the spray boom, the plants are shaken without damages in such a way that the whole plants are wet also on the underside of leaves and all parts in the center and at the foot.

The inorganic wetting agent guarantees an even distribution on the leafs of the crop in form of a film, created by negative charged water and not only by micro-drops what is ensuring a complete moistening.

The negative electrical charge of the water film guarantees that the immediately after sprinkled ozonated water with a positive Dipole in form of a mist reaches all parts and zones of the plant-leafs.

2. Spray-treatment of plants with ozonated water, with the help of a new ozone spray-valve mixing technique, respectively with a Venturi valve and pressure turbine and air-jet whirl technique and UV-C irradiation.

Ozone produced out of Oxygen (produced by air-separator 98% pure oxygen) by the method of cathodic corona discharge is injected by aspiration in the water leading to the water tank of the boom-sprayer with a pressure preferably between 1.5 and 2.5 bar by a Venturi valve, and consequently the ozone containing water is mixed in a specially designed pressure turbine with a pressure of preferentially 4.7 to 6 bar in such away that

the ozone-gas bubbles consist only in a microform and that they bond well with the water in the desired concentration.

This new method prevents a rapid off gassing of ozone and guarantees that the ozone gas remains in water solution during the spraying performance with pressures between preferentially 4 and 10 bar.

Spraying is done with spray pressures preferentially between 4 and 10 bar.

Hereby, different spray and air-nozzles are used.

The air nozzles create with the special adaptable spray-boom-cover an air-whirl which is shaking the to be treated plants in such a way, that the ozone containing water can reach all plant – parts and above all as well the underside, the heart and the foot of the leafy plant.

The previous moistening with negative charged water results in the fact that ozone with its positive dipole attaches itself immediately to negative water molecules in the water film of the pre-sprinkling, performing completely its oxidative properties on all parts of the plants simultaneously and with the same results.

With the neet contact of ozonated water, with a concentration preferably of 2 mg/liter up to 40 mg/liter in the spray solution (depending of pathogenic pressure and plant variety), fungus, yeasts, bacteria, their spores und virus, protozoa and insects are eliminated.

Hereby the CT factor (concentration x contact time in minutes) plays a very important role.

Each plant pathogen has its specific CM-factor, which lies preferentially between approx. 10 and 200 mg Min.

The ozone concentration in water is adjusted according to the corresponding expected pathogen image.

The reaction time of Ozone lies between 20 second and 20 minutes.

The half-life time of Ozone in water is approximately 2 minutes, in other words the ozone concentration in water is reduced by half every 2 minutes.
Ozone not used evaporates quickly again as oxygen.

The radiation with UV-C light with lamps with a power of 35 Watt and a wavelength of 254 Nanometers and/or 185 Nanometers represents, with the creation of highly reactive hydroxy-radical compounds in the moist surrounding of the spray-fog, an additional microbial biocidal hurdle effect.

The use of ozonated water in combination with UV-light for crop protection purposes is extremely effective, cheap and environmentally friendly and may also be used in ecological growing.

The efficiency degree in our own field trials was shown to be up to 92%, which complies with the norms of conventional crop protection methods or even better.

Ozone treatments in combination with UV-C light for crop protection create no residues.

All ozone transforms in a short period of time (hours) again in oxygen.

Ozone and UV-C light in short exposure do not harm plants in any way, since Ozone and UV-light only are able to enter molecular cell membranes of microbes and not cell walls of plants, because the contact time is too short.

Ozone treatments and UV-C irradiation for crop protection do not create resistancy in pathogens, since the reactivity of the biocides is based exclusively on oxidative processes.

Ozone treatments for crop protection are environmentally friendly, since all Ozone molecules are disintegrating again to Oxygen.

The use of Ozone in combination with UV-light is substantially cheaper than conventional chemical spray-methods, because there is no use of expensive chemicals anymore.

The investment in the hardware for the spray-technology is approximately double as high as in conventional Spray-Machines.

The average depreciation time of a sprayer with Ozone technology is approx. 4 years. The life span is minimal 10-15 years.

In such a period more than $\frac{3}{4}$ of the spraying costs can be saved in comparison with traditional conventional chemical crop-treatment methods.

THE IMPLEMENTATION OF THE INVENTION

For the implementation of the method for the control of fungal- bacterial- viral- and insect-attacks in crop protection with the means of dipole electrical air-jet technology, ozonated water and UV-C irradiation are preferentially one or two hydraulic mounted telescopic boom sprayers or a pulled turbine sprayer necessary, as used in orchards or vineyards.

The sprayers are connected with the back- or the front - hydraulic system or the hook system of a tractor which has a power of preferentially 65 HP and more.

In all cases the tank as specified is filled with 500 or up to 2000 liters of natural clean water which does not contain too much calcer.

The driving shafts to power the spray-pressure pumps and the air-blowers or the air-compressors are connected to the PTO-shaft of the tractor (back and front)

The petrol engine driven electrical generator with preferentially minimal 8 KVA power output is started.

The cables to the electrical transformer on the mounted sprayer in front connected to the switchboard.

The transformer is switched to the position Direct Current DC with a voltage of 1000 to 2000 Volts.

The electrical current to the anode in the insulated tank is now established, and the water and the wetting agent are charged with a negative load, which is necessary to create a negative charge in the water-film during the pre-moistening of the plants.

To the pre-moistening water will be a wetting agent added with 2% in the solution.

The Oxygen-Concentrator and the Ozone-Generator with cathodic discharge will be switched on.

Ozone is now produced, and with a preferential pressure of 1,5 to 2,5 bar injected with a Venturi valve by suction with the help of a pressure pump with preferentially 5 to 8 KVA power performance driving the water-circulation system of the sprayer at the back. Hereby, the under pressure staying ozonated water passes through the integrated turbo-mixer, which is bonding the ozone in microform to the water molecules and leads to a better mixture and stronger bondage of the ozone to the water.

After approx. 5 minutes the desired and established concentration of ozone is reached in the tank and the ozone-generator is regulating itself automatically in ideal position.

In case the established ozone-concentration in the spray-tank is diminishing the ozone-generator starts to work again automatically.

This automatism is regulated by an ozone-measurement probe and an electrical steering unit, which is installed in the switchboard of the spray-machine.

The UV-C lamps are connected to the electrical circuit and are controlled by an automatic switch.

The spray-machines are yet ready for operation.

The PTO driving shafts to the sprayers at the front- and at the back are now put in motion.

The spray-pressure and the pressure of the whirled air are establishing themselves, preferentially at 4 up to 10 bars, depending on the relevant application.

With extended and height adapted spray-booms and correct regulated spraying pressure and spray-volume of approx. 30-80 liters per minute, the spray process can start.

With the spray-equipment at the front hydraulic of the tractor the negative charged pre-moistening-water with the moistening agent (approx. 2% in solution) is sprayed through the driving shaft driven sprayer-pump (5-8 HP) via the special spray-water nozzles on the to be treated plants and at the same time the plants are shaken by air from the special air-nozzles generated by the air-blower and/or air-compressor under the protective spray-boom-cover in such a way that the spray-mist is wettening all parts of the plants inclusive the underside, the core and the foot parts.

After seconds the ozone spraying from the spray-equipment on the back of the tractor is following (speed 3-5 km/h).

The ozone containing spray-solution (milky appearance) is sprayed over the previously with negative charged water treated plants with the same method via the PTO-shaft driven pressure pump and the special spray nozzles with preferentially 4 to 10 bar pressure (different according species of plant and pathogens)

Hereby, a shaking of the crop is achieved at the same time through the air-nozzles protected by the spray-boom cover in such a way, that ozonated water preferentially with a concentration of 3-40 mg/liter is coming in contact with all parts of the plants.

Through the negative charge of the pre-moistening water an intense electrostatic bonding with the ozone-spray fog with a positive dipole is achieved on all parts of plants, which is increasing the oxidative action of the ozone and which guarantees that the oxidation of pathogens happens on all surfaces.

The ultraviolet beams mounted at the front and back of the sprayers increase substantially the effect of the ozone application through the creation of highly oxidative hydroxy-radical species transformed in the humid atmosphere of the spray fog. The hurdle-principle, whereby cellular defence-mechanisms of pathogens fail when attacked by applying more than one biocide, is functioning very well.

With this new preventive spray-technology and with the use of ozonated water it is possible to control, 92% of all fungus, yeast, bacteria, virus and insects.

The described invention is a new breakthrough spraytreatment-methode for crop-protection.

The technology complies with all requirements of a contemporary modern crop management and can even be used in the ecological and bio-production.

The new spray-technology-process and the used technique are simple, cheap and environmentally friendly and do not create residues on food-plants nor do they create resistances in fungus, yeast, virus and insects, as those are well known effects of conventional chemical treatments.

PULLED AND MOUNTED EQUIPMENTS

Tractor (minimal 65 HP) with front- and back-hydraulic, with adaptable front-and back PTO-shaft-drives, with closed driver's cabine with overpressure ventilation and ozone-filter.

The Pre-Spray Equipment contains the following technical main-parts

- 1A. Three (3) point hydraulic chassis with tank holders.
- 2A. PTO shaft connection or electro meter
- 3A. Tank for water filling
- 4A. Sprayer Pressure – Pump
- 5A. Two (2) pressure Manometers adjustable (entrance and exit pressure)
- 6A. Two (2) lateral spray –booms with preferable twenty (20) UV – lamps minimum
35 Watts
- 7A. One (1) anode
- 8A. One (1) Transformer for alternating and direct current for the negative charging of
the spray water.
- 9A. One (1) Air – blower or air –compressor with pressure tank for the creation of the
air – jet stream.
- 10A. Divers spray nozzle for water and air.
- 11A. One (1) water dosing valve.
- 12A. One (1) reverse pressure valve for water mixer in the tank with handle.
- 13A. One (1) filling gate for water with pressure seal.
- 14A. One (1) Tank drainage gate valve.
- 15A. One (1) Spray boom cover adaptable for the precise guidance of spray- mist
air-whirl- stream and UV light.
- 16A. One (1) PTO shaft connection for spray pressure – pump.

The ozone water spray equipment contains the following technical main parts:

- 1B. Three (3) point hydraulic chassis with tank holders.
- 2B. One (1) electrical generator with control box.
- 3B. One (1) Air separator for the production of oxygen.
- 4B. One (1) generator with cathodic discharge from 98% oxygen.
- 5B. One (1) ozone-dosing valve
- 6B. One (1) Ozone in water concentration analysis
- 7B. One (1) Venturi valve for the injection of ozone in water.
- 8B. One (1) electrical pressure pump for water tank.
- 9B. Two (2) pressure manometer (entrance and exit pressure pump with 2 gate valve.
- 10B. Ozone –gas mixer turbine
- 11B. One (1) water tank for ozonated water
- 12B. One (1) driving –chassis or mounting device for tractor hydraulic
- 13B. PTO shaft or electrical driven water pressure pump made of rust face steal for the spraying of ozone – water.
- 14B. Two (2) lateral telescopic spray – booms with minimum 20 mounted 35 Watts UV – C lamps.
- 15B. Divers Ozone Water Spray and air – jet whirlstream nozzles.
- 16B. One (1) PTO shaft or electrical driven air – blower or air – compressor with pressure tank to perform the air whirlstream via the nozzles.
- 17B. One (1) water dosing valve
- 18B. Two (2) pressure manometers (entrance and exit – pressure)
- 19B. One (1) reverse pressure valve for water – mixer in tank
- 20B. One (1) filling gate for water in the tank with pressure seal